

Description:

Rainwater filter for bigger roof areas. The 3P Volume Filter has to be installed in a pilot shaft (Ø 48 inches). Normally standard concrete shafts are used. The filter can be delivered to the site yet pre-assembled in the shaft.

Two step cleaning system, therefore high level of filtering efficiency, independent of flow rate.

Due to the steep inclination of the filter cart-ridge the dirt is continuously cleaned away into the sewer. The connection to the sewer is installed at the shaft. The dirt falls down on the bottom of the shaft and is washed away with the next strong rainfall.

Relative connection capacity according to DIN 1986: for roof areas up to 15,000 ft² at a rainfall intensity of 80 gal/(sxha)

Because of a Bypass-Installation a bigger area can be connected.

Inlet rainwater: 2 x 10"
Outlet to storage: 8"
Outlet to sewer: 10"


Blinding plates are included
Height difference between inlet and outlet: 12", measured mid of the tube

The filter has to be cleaned depending on the contamination 1 - 2 times during the year



How it works:

1. The incoming rainwater is backed up in the collection pan and is then equally distributed across the cascades = principle of overflow
2. Pre cleaning through the cascades, coarse dirt particles are led across the primary filter cascades directly to the sewer
3. Pre-filtered water then flows over the secondary filter sieve (Mesh size 0,4 x 1 mm), due to the special mesh structure and the steep situation of the sieve, any dirt falls directly down onto the bottom of the shaft, in case of heavy rainfalls, the filter has more loss, as the water washes away the filtered dirt into the sewer
4. The cleaned water is being absorbed in the lower collection pan and directed through a tube 8" into the storage
5. Dirt goes to the sewer through the shaft



Technical Data:

Filter according to DIN 1989-2, Typ C


Inlet rainwater: 2 x 10"
Outlet to storage: 8"
Outlet to sewer: 10"

Height difference between inlet and outlet: 12", mid of tube


Material Filter corpus: Stainless steel 4016
Material Filter sieve: Stainless steel 1.4301
Mesh size: 0,4 x 1 mm

Legs = Thread rods M10 with screw nut made of stainless steel, Length 10"

Weight: 39,5 kg



A 26.4 in
B 26.8 in
C 22.6 in
D 38.6 in
E 12.6 in
F 10.8 in
G 34.6 in





Example 1:

Installation of the filter in a pilot shaft



Example 2:

Installation of the filter in front of several concrete tanks which are situated in a row




Source: Prof. Dr.-Ing. Mathias Uhl Muenster University of Applied Sciences

80% of the average intensity of rainfall in Germany is under 15 l/(sxha), resulting a volume flow rate of 3,65 l/s with a roof area of 2433 m².

Diameter of tube	maximum flow rate	connectable area max. 200 l/(sxha)	connectable area max. 300 l/(sxha)
In	gal/s	ft²	ft²
10	19.3	39,000	15,000

Optimal installation:

If the size of the roof or the diameters of the tubes should vary from the specifications / requirements, you can make an installation according to the DIN as demonstrated below.



Advice:

On demand the filter can be equipped with only one inlet. Please indicate in order. The hole then will be closed with a blinding plate.

Packing unit
3P Volume Filter VF6:
Pallet: 3 pieces