

MULTIPLE FUNCTIONS

ALL-IN-ONE PUMP

The Econ FP is compact, easy to program and can respond to flow input from a variety of water conditioning equipment



Water Meter

The pump will accept a pulse input from a dry contact water meter and has adjustable operating times of 0.1-1, 0.5-5, 1-10, 2-20 or 6-60 seconds per pulse.

Flow Switch

Accepting a signal from a dry contact flow switch, the pump will run at the selected speed when the switch is closed and stop when the switch opens.

12-24 VAC/VDC Input

The pump will run at the selected speed when it receives a 12-24 VAC/VDC signal from a water softener or other equipment.

Up to 30 gpd @ 80 psi

Wall Mountable

Adjustable from 10% to 100%

Effortless Tube Replacement








Econ FP is ideal for light duty water conditioning applications

- Patented quick release pump head design
- Solid one piece tube construction
- **UL & cUL listed**
- NSF 61 & 372 listed for USA & Canada
- 4 lbs
- 5.3" I x 3.6" w x 5.8" h

Optional Mounting Accessories



Mounting Kit EC303 For Stenner Tank or wall mount



Stand EC304 For horizontal display or wall mount

Outputs

Item Number Prefix	Pump Tube	Roller Assembly	Gallons per Day	Pressure psi	Liters per Day	Pressure bar
E20PHF	F	White	4.5	80	17.0	5.5
E20PHG	G	Black	16.0	80	60.6	5.5
E20PHH	Н	Black	30.0	80	113.8	5.5
			Approximate Maximum Outputs @ 50/60Hz			

Build An Item Number

1

Select Item Number Prefix from output chart above

Leave blank if not ordering a tank system

Tank

\$7N 7.5 Gallon White

S1N 15 Gallon White

S3N 30 Gallon White

NOTE: Tanks also sold separately.

Voltage & Hertz/Cord

7 120V 60Hz; 6' cord

8 120V 60Hz; 10' cord

Suction & Discharge Tubing

1 1/4" White

Tube Material

S Santoprene®

This information is not intended for specific application purposes. Stenner Pump Company reserves the right to make changes to prices, products, and specifications at any time without prior notice. FEFP 0213





