AQUIFER LOW PROFILE CISTERNS

PART NO.	CAPACITY	DESCRIPTION	WEIGHT	TANK DIMENSIONS
ACT1000-LPB	1000 Gallon	Low Profile Cistern w/Burial Lid	559	98" x 111" x 36"
ACT1000-LPG	1000 Gallon	Low Profile Cistern w/Ground Access Assembly	595	98" x 111" x 36"
ACT1500-LPB	1500 Gallon	Low Profile Cistern w/Burial Lid	702	98" x 111" x 48"
ACT1500-LPG	1500 Gallon	Low Profile Cistern w/Ground Access Assembly	738	98" x 111" x 48"
ACT2000-LPB	2000 Gallon	Low Profile Cistern w/Burial Lid	917	98" x 158" x 45"
ACT2000-LPG	2000 Gallon	Low Profile Cistern w/Ground Access Assembly	953	98" x 158" x 45"
ACT2500-LPB	2500 Gallon	Low Profile Cistern w/Burial Lid	1031	98" x 158" x 54"
ACT2500-LPG	2500 Gallon	Low Profile Cistern w/Ground Access Assembly	1067	98" x 158" x 54"

AQUIFER LOW PROFILE CISTERN ACCESSORIES

PART NO.	DESCRIPTION	WEIGHT	DIMENSIONS
ACT-16053	Aquifer 24" Burial Lid & Gasket	17	35" x 8"
ACT-16052	Aquifer Ground Access Assembly - 28" Riser, 24" Locking Lid & Gasket	53	34" x 38"











Low Profile Cistern Tanks



Aquifer Low Profile Cistern Tanks

- · Strong, durable, quality construction
- Low profile design, for bulk collection and storage of potable or non-potable water
- Bury up to 28" deep
- · Tank can be backfilled empty
- Tank can be used in both below and above ground applications
- Manufactured from high-density polyethylene with U.V. inhibitors
- Tanks can be stacked for shipping and storage
- Sectional ribbing designed to withstand up to 400 PSF load pressure
- Manufactured from FDA compliant resins
- Low profile design with multiple fitting flats to accommodate a variety of plumbing configurations
- Manufactured for containment of liquids up to 1.7 specific gravity
- Serial code, fully documented from date of manufacture
- Aquifer Installation Guidlelines, Product Specifications and Warranty information is available at www.denhartogindustries.com

The Ace Roto-Mold Difference

Only Ace Tanks feature a custom-molded gasket in the lid. Manufactured from extruded Nitrile rubber, the gasket snaps into the lid and ensures a water-tight seal.





Exclusive Lid Design Only Ace Tanks have double-walled access covers that lock securely to the tank body and can be secured using nylon ties, eliminating the need for metal fasteners that can corrode and fail.



Ground Access Assembly 28" riser and Locking Lid with flats for fitting installation.

> Closed Cell Foam Gasket provides secure seal between lid or riser and tank.



- Burial Lid with flats to accomodate up to a 3" fitting.

Fitting Flats on tank top accept fittings up to 3".

Fitting Flats

accept fittings up to 4", allow additional drainage options and enable the connection of multiple tanks in a series.



Support Columns Molded in columns and intermediate 4" PVC supports throughout the tank provide additional structural strength.

