

# DURABLE. DEPENDABLE. OPEN TOP TANKS.



The RainFlo above ground open top water tanks are ideal storage solutions that are simple to use and maintain. Open top tanks are available in two styles which feature removable tops for easy installation, access, and maintenance. For reduced shipping costs, the open top tanks can be shipped with components stored inside on a single pallet. The stackable open top tank design reduces shipping costs further by nesting multiple tanks. Ranging from 600 to 2000 gallons, both styles feature a food grade lining and include multiple features for security and convenience.

## Key Features:

- Removable tops for easy tank installation, access, and maintenance
- Manufactured from polyethylene with an FDA approved food grade lining
- Optional connection kit to plumb multiple tanks together for unlimited storage capacity
- Up to 4" inlet, 1.5"-2" outlet
- 18" access lid
- 10-year warranty (TOT), 7-year warranty (TST)

## TANK STYLES




Open Top Tank (TOT)



Open Top Stackable Tank (TST)

## DIMENSIONS



Part Number	Tank Size (US gallons)	Dimensions (A x B x C)	Access Opening	Inlet	Outlet	Estimated Weight (lbs.)
<b>Open Top (TOT)</b>						
TOT-600BK	600	56" x 77"	18"	up to 4"	.75"	87
TOT-800BK	800	62" x 88"	18"	up to 4"	1.5"	128
TOT-1000BK	1000	67" x 97"	18"	up to 4"	1.5"	140
TOT-2000BK	2000	79" x 122"	18"	up to 4"	2"	357
<b>Open Top Stackable (TST)</b>						
TST-600BK	600	61" x 74" x 49"	18"	up to 4"	.75"	90
TST-1000BK	1000	84" x 79" x 68"	18"	up to 4"	1.5"	172

\*For a complete list of tanks, please contact your representative

## INSTALLATION AND MAINTENANCE TIPS

- Ensure the tank is placed on a level base, free of sharp objects.
- Thoroughly rinse the tank before installation to remove debris from shipping.
- Tanks should be periodically cleaned as sediment settles.
- Tank lid should be secured at all times. The tank access lid includes a location to secure a lock for safety.



Align molded directional arrows to easily install tank lid using the nylon screws provided



Lockable access lid for added safety